

SKM 75GD123D



SEMITRANS® 6

Standard IGBT Modules

SKM 75GD123DL

SKM 75GD123D


SKM 75GDL123D

Features

- MOS input (voltage controlled)
- N channel, homogeneous Si
- Low inductance case
- Very low tail current with low temperature dependence
- High short circuit capability, self limiting to $6 \times I_{Cnom}$
- Latch-up free
- Fast & soft inverse Cal diodes
- Isolated copper baseplate using DCB Direct Bonding Technology
- Large clearance (9 mm) and creepage distance (13 mm)

Typical Applications

- Switched mode power supplies
- DC servo and robot drives
- Three phase inverters for AC motor speed control
- Switching (not for linear use)



GD

GDL

Absolute Maximum Ratings		$T_c = 25\text{ }^{\circ}\text{C}$, unless otherwise specified		
Symbol	Conditions		Values	Units
IGBT				
V_{CES}	$T_j = 25\text{ }^{\circ}\text{C}$		1200	V
I_C	$T_j = 150\text{ }^{\circ}\text{C}$	$T_{case} = 25\text{ }^{\circ}\text{C}$	75	A
		$T_{case} = 80\text{ }^{\circ}\text{C}$	50	A
I_{CRM}	$I_{CRM}=2 \times I_{Cnom}$		100	A
V_{GES}			± 20	V
t_{psc}	$V_{CC} = 600\text{ V}; V_{GE} \leq 20\text{ V}; T_j = 125\text{ }^{\circ}\text{C}$ $V_{CES} < 1200\text{ V}$		10	μs
Inverse Diode				
I_F	$T_j = 150\text{ }^{\circ}\text{C}$	$T_{case} = 25\text{ }^{\circ}\text{C}$	75	A
		$T_{case} = 80\text{ }^{\circ}\text{C}$	50	A
I_{FRM}	$I_{FRM}=2 \times I_{Fnom}$		100	A
I_{FSM}	$t_p = 10\text{ ms}; \sin.$	$T_j = 150\text{ }^{\circ}\text{C}$	550	A
Module				
$I_{t(RMS)}$			100	A
T_{vj}			- 40 ...+ 150	$^{\circ}\text{C}$
T_{stg}			- 40 ...+ 125	$^{\circ}\text{C}$
V_{isol}	AC, 1 min.		2500	V

Characteristics			T _c = 25 °C, unless otherwise specified			
Symbol	Conditions		min.	typ.	max.	Units
IGBT						
V _{GE(th)}	V _{GE} = V _{CE} , I _C = 2 mA		4,5	5,5	6,5	V
I _{CES}	V _{GE} = 0 V, V _{CE} = V _{CES} T _j = 25 °C			0,4	1,2	mA
V _{CE0}	T _j = 25 °C			1,4	1,6	V
	T _j = 125 °C			1,6	1,8	V
r _{CE}	V _{GE} = 15 V T _j = 25°C			22	28	mΩ
	T _j = 125°C			30	38	mΩ
V _{CE(sat)}	I _{Cnom} = 50 A, V _{GE} = 15 V T _j = °C _{chiplev.}			2,5	3	V
C _{ies}	V _{CE} = 25, V _{GE} = 0 V f = 1 MHz			3,3	4,3	nF
C _{oes}				0,5	0,6	nF
C _{res}				0,22	0,3	nF
t _{d(on)}	R _{Gon} = 22 Ω	V _{CC} = 600V I _{Cnom} = 50A T _j = 125 °C V _{GE} = ± 15V		44	100	ns
t _r				56	100	ns
E _{on}			8		mJ	
t _{d(off)}	R _{Goff} = 22 Ω			380	500	ns
t _f				70	100	ns
E _{off}				5		mJ
R _{th(j-c)}	per IGBT				0,32	K/W

SKM 75GD123D



SEMITRANS® 6

Standard IGBT Modules


SKM 75GD123DL
SKM 75GD123D
SKM 75GDL123D

Features

- MOS input (voltage controlled)
- N channel, homogeneous Si
- Low inductance case
- Very low tail current with low temperature dependence
- High short circuit capability, self limiting to $6 \times I_{cnom}$
- Latch-up free
- Fast & soft inverse Cal diodes
- Isolated copper baseplate using DCB Direct Bonding Technology
- Large clearance (9 mm) and creepage distance (13 mm)

Typical Applications

- Switched mode power supplies
- DC servo and robot drives
- Three phase inverters for AC motor speed control
- Switching (not for linear use)



GD GDL

Characteristics		min.	typ.	max.	Units
Symbol	Conditions				
Inverse Diode					
$V_F = V_{EC}$	$I_{Fnom} = 50\text{ A}; V_{GE} = 0\text{ V}$ $T_j = 25\text{ }^{\circ}\text{C}_{chiplev.}$ $T_j = 125\text{ }^{\circ}\text{C}_{chiplev.}$		2 1,8	2,5	V V
V_{F0}	$T_j = 25\text{ }^{\circ}\text{C}$ $T_j = 125\text{ }^{\circ}\text{C}$		1,1	1,2	V V
r_F	$T_j = 25\text{ }^{\circ}\text{C}$ $T_j = 125\text{ }^{\circ}\text{C}$		18	26	mΩ mΩ
I_{RRM}	$I_{Fnom} = 50\text{ A}$ $T_j = 125\text{ }^{\circ}\text{C}$		35		A
Q_{rr}	$di/dt = 800\text{ A}/\mu\text{s}$		7		μC
E_{rr}	$V_{GE} = 0\text{ V}; V_{CC} = 600\text{ V}$		2,2		mJ
$R_{th(j-c)D}$	per diode			0,6	K/W
Module					
L_{CE}				60	nH
$R_{th(c-s)}$	per module			0,05	K/W
M_s	to heat sink M5				Nm
M_t	to terminals	4		5	Nm
w				175	g

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.

SKM 75GD123D



SEMITRANS® 6

Standard IGBT Modules


SKM 75GD123DL
SKM 75GD123D
SKM 75GDL123D

Features

- MOS input (voltage controlled)
- N channel, homogeneous Si
- Low inductance case
- Very low tail current with low temperature dependence
- High short circuit capability, self limiting to $6 \times I_{cnom}$
- Latch-up free
- Fast & soft inverse Cal diodes
- Isolated copper baseplate using DCB Direct Bonding Technology
- Large clearance (9 mm) and creepage distance (13 mm)







Typical Applications







- Switched mode power supplies
- DC servo and robot drives
- Three phase inverters for AC motor speed control
- Switching (not for linear use)




GD GDL

Z_{th}			
Symbol	Conditions	Values	Units
$Z_{th(j-c)I}$			
R_i	$i = 1$	240	mk/W
R_i	$i = 2$	68	mk/W
R_i	$i = 3$	9,2	mk/W
R_i	$i = 4$	2,8	mk/W
τ_{ui}	$i = 1$	0,06	s
τ_{ui}	$i = 2$	0,0228	s
τ_{ui}	$i = 3$	0,0013	s
τ_{ui}	$i = 4$	0,0002	s
$Z_{th(j-c)D}$			
R_i	$i = 1$	400	mk/W
R_i	$i = 2$	168	mk/W
R_i	$i = 3$	28	mk/W
R_i	$i = 4$	4	mk/W
τ_{ui}	$i = 1$	0,0831	s
τ_{ui}	$i = 2$	0,0112	s
τ_{ui}	$i = 3$	0,0013	s
τ_{ui}	$i = 4$	0,08	s






CASED68




Case D 56a



Case D 67

GD



Case D 73

GDL